PLAT & SURVEY

LOCATED IN THE EAST HALF OF THE SOUTHEAST QUARTER, SECTION 26, TOWN 9 SOUTH, RANGE 2 WEST, MADISON TOWNSHIP, WILLIAMS COUNTY, OHIO.

NE CORNER, SE 1/4, SEC 26 LINE 1/4 PATION REFERENCE TO DEED VOL. 267 PG 223 5 N 89° 49' 00" E 1308.0 AND 1278.0 30.0 FENCE FOUND IRON BOLT EXISTING FOUND RR SPIKE OVER STONE 27.16 ACRES A FOUND IRON PIPE OVER STONE 00 PLACED 5/8" REBAR 9 X PLACED PK NAIL °o 30.0 REFERENCE TO SURVE 1277.58 VOL. 6R PG. 94 49' 00" W 1307.58 3 36 0 ° SEC CO. RD. P-Z 29" W 1307.18 SE CORNER, SEI/4, SW CORNER, E 1/2, SE 1/4, SEC 26 SEC 26

I hereby certify that I have surveyed the premises and prepared the above plat and that said plat is correct to the best of my knowledge and belief. I dimensions are shown in feet and decimal parts thereof. This survey has een recorded in Vol. Page // of the Williams County Record of Surveys.

DENNIS

BELL

6717

SCALE 1" = 300.0 DATE 5/24/85 JOB NO. OS - 70 - 85

Dennis M. Bell Reg. Surveyor #6717

BELL ENGINEERING LIMITE
1211 W. HIGH - P.O. BOX 565 ENGINEERING LIMITED OHIO 43506 BRYAN. (419) 636 - 2585